U·LINK



UL-4DIR25FFC-IP

4MP Outdoor Dome Camera VF Lens

POWERING THE FUTURE



Features

- 1/1.8" SONY Starvis Back-illuminated CMOS Sensor.
- H.265+/H.265/H.264+/H.264 Compression Method.
- Suport Warm White (4000K), Up To 25m.

Specification

Camera

Image Sensor	1/1.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	4MP
Effective Pixels	2712x1538p
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG
Audio Compression	G711A/U,AAC
TV System	PAL/NTSC
Electronic Shutter Time	Auto: 1/3-1/100000Sec
Minimun Illumination	Color: 0.0001 Lux @ (F1.0, AGC On), 0 Lux With White Light
S/N Ratio	60dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional

Lens

Focal Length & FOV	2.8mm, Horizontal FOV 106°, Vertical FOV 56°, Diagonal FOV 127°
	4mm, Horizontal FOV 87°, Vertical FOV 44°, Diagonal FOV 104°
	6mm, Horizontal FOV 54°, Vertical FOV 29°, Diagonal FOV 63°
Lens Type	Fixed Focal Lens 2.8, 4, & 6mm Optional
Focus Control	Fixed
Aperture	F1.0
Pixels	4MP

Night Vision

Supplement Light	Support Warm Light LED 4000K, Up To 25m
Supplement Light Distance	N/A
Supplement Light Status	Auto Control
Supplement Light Power On	Smart, Manual & Timed Mode

Network

Ethernet	RJ-45 (10/100Base-T)
Wireless	N/A
Protocol	TCP/IP, IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, PPPOE, NTP, SMTP, UDP, SNMP, Qos, 802.1x
ONVIF	Support ONVIF 19.12 (Profile S/T/G)
P2P	Yes
POE	Internal, Support IEEE 802.3af
Video Delay	0.35 (Within The Lan)
Main Stream 1	2688x1512@30fps
Main Stream 2	2560x1440@30fps
Main Stream 3	1920x1080@30fps - 1280x720@30fps
Sub Stream 1	1280x720@30fps
Sub Stream 2	720x480@30fps
Sub Stream 3	352*288@30fps
Tri Stream	1280x720@30fps - 720x480@30fps - 352x288@30fps
IE Browser	IE8-11, Google Chrome, Firefox, Mac Safari
Smart Phone	IPhone, Android

AI Function

Intelligent Analysis	Intrusion Detection (Based On Human & Vehicle Detection), Line Cross Detection (Based On Human & Vehicle Detection), Loiter Detection (Based On Human Detection), People Gather Detection (Based On Human Detection), Motion Detection Based On Human Detection, Upload Face Capture To FTP



Camera Features

Day Night	Color
Image Config	Saturation, Brightness, Contrast, Sharpness, Mirror, 3D NR, White Balance, Anti Flicker, Video Tampering, HLC, Distortion
Full Color	Support
Corridor Pattern	Support
Defog Mode	Support
ROI	Support
BLC	Support
WDR	140dB
Motion Detection	Support (Support Enable The Detection Based On Human Movement Only)
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	English, Russian, Korean, Polish, French, Japanese, Spanish, Portuguese, Italian, Hebrew, Ukrainian, Arabic, Vietnamese, Thai, Hungarian

Interface

Audio	Optional 1 Built-in MIC
Alarm	Optional 1CH Input/Ouput
SD Card Slot	Optional External, Support Max 1TB, Built-in 4G Storage
RS485	N/A

General

Housing	Metal ,IP67
Anti-Cut Bracket	No
IR Cut Filter	Yes
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension WxH	Φ115x113mm
Weight	800g



U·LINK

POWERING THE FUTURE

Email:
info@u-link.uk

Address:
Sydney House, 62 Lancaster Way, Ely,
Cambridgeshire, CB6 3NW, UK

Website:
https://u-link.uk