U·LINK



UL-5BIR60M-IP

5MP Outdoor Bullet Camera Motorized Lens

POWERING THE FUTURE



Features

- Pro IP Bullet Camera.
- 1/2.7" SONY Starvis Back-illuminated CMOS Sensor.
- H.265+/H.265/H.264+/H.264 Compression Method.
- 2.7-13.5mm Motorized Lens.
- IR Distance 60m Max.
- With Internal POE & External SD Card Slot.

Specification

Camera

Image Sensor	1/2.7" SONY Starvis Back-illuminated CMOS Sensor
Resolution	5MP
Effective Pixels	2616x1964p
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec, NTSC 1/30-1/10000Sec
Minimun Illumination	0.01 Lux, 0 Lux With IR On
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Auto/Manual Iris	Yes

Lens

Focal Length	2.7-13.5mm Motor Zoom
Focus Control	Auto
Lens Type	Auto
Pixels	5MP

Night Vision

Infrared LED	42μ x 2 PCS
Infrared Distance	60m
IR Status	Auto Control
IR Power On	Smart, Manual & Timed Mode

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP ,PPPoE, NTP, SMTP, UDP, SNMP
ONVIF	Support ONVIF 19.12 (Profile S/T/G)
P2P	Yes, Support QR Code
POE	Internal, Support IEEE 802.3af
Main Stream 1	2592x1944@30fps
Main Stream 2	2560x1440@30fps
Main Stream 3	1920x1080@30fps - 1280x720@30fps
Sub Stream 1	1280x720@30fps - 720x480@30fps
Sub Stream 2	352x288@30fps
Tri Stream	1280x720@30fps - 720x480@30fps - 352x288@30fps
IE Browser	E8-11, Google Chrome, Firefox, Mac Safari
Smart Phone	iPhone, IPad, Android, Android Pad

AI Function

Intelligent Analysis	Face Detection, Intrusion Detection, Line Cross Detection, Loiter Detection, People Gather Detecion, Motion Detection Based On Human Detection



Camera Features

Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation, Brightness, Contrast, Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control), Video Tampering, HLC, Distortion
Full Color	Support
Corridor Pattern	Support
ROI	Support
BLC	Support
WDR	HDR: 120dB
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands, Czech, Vietnamese

Interface

Audio	Optional 1 Built-in MIC
Alarm	Optional 1CH Input/Output
SD Card Slot	Optional External, Support Max 512GB, Built in 4G Storage

General

Housing	Metal ,IP67
IR Cut Filter	Yes
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 1100mA
Dimension WxHxD	Φ220x109x106mm
Weight	2.15Kgs



U·LINK

POWERING THE FUTURE

Email:
info@u-link.uk

Address:
Sydney House, 62 Lancaster Way, Ely,
Cambridgeshire, CB6 3NW, UK

Website:
https://u-link.uk