U·LINK



UL-8NVR-IP

8CH HD/5MP with 1SATA Interface NVR

POWERING THE FUTURE



Features

- Third-Party Network Cameras Supported.
- Up to 5MP Resolution Recording & Playback.
- HD & VGA Output, HD Port Up To 1920x1080p.
- Support H.265+/H.265/H.264+/H.264 Video Format.
- Support 1SATA Up to 8TB Capacity.
- Support 8 Independent POE Network Interfaces.

Specification

System

Main Processor	ARM Cortex A7 Processor
Operating System	Embedded LINUX

Video

Input	8CH (2592x1944, 2048×1536, 1920×1080, 1280×960, 1280×720, etc)
Output	1 VGA, 1 HD

Audio

Output	1 Port 3.5mm (Linear, 1kΩ)
Audio Bit Rate	64kbps
Audio Compression Standard	G711u, G711a, ADPCM_DVI4

Alarm

Sensor Input	No
Output	No
Motion Detection	8CH, MD Zones: 396 (22×18)
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer & Screen Tips

Display

HD Output1	1920x1080/60Hz, 1280x1024/60Hz, 1280×720/60Hz, 1024x768/60H7
VGA	1920x1080/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Display Split	8CHxD1/8CHxD1/4CH×D1/1CH×1080P/1CHx3MP/1CH×4MP/1CH×5MP
Digital Zoom	Yes
OSD	Camera Title, Time, Recording, Motion Detection, Event Alarm

Recording

Video Compression	H265/H264/H265+/H264+
Resolution	5MP (2592×1944), 4MP (2688×1520/2560×1440), 3MP (2048×1536), 1080P (1920x1080), 960P (1280x9601), 720P (1280×720) D1 (720x576/720×480)
Record Rate	PAL:5MP(@9x25fps, 4MP@9x25fps, 3MP@9x25fps, 1080P@9x25fps, 960P@9x25fps, 720P@9×25fps, D1@9x25fps NTSC: 5MP@9×30fps, 4MP@9×30fps, 3MP@9×30fps, 1080P@9x30fps, 960P@9x30fps, 720P@9×30fps, D1@9×30fps
Record Mode	Manual\Timer\Motion Detection\Alarm Input\Smart Alarm

Playback & Backup

Local Sync Playback	1CH 5MP@30fps, 1CH 4MP@30fps, 2CH 3M@30fps, 4CH 1080P@20fps, 4CH 960P@30fps, 4CH 720P@30fps
Decode Capability	4CH 1080p@20fps (Readme)
Remote Sync Playback	Yes
Search Mode	All, Channel, Manual, Time, Date, Motion Detection, Event Alarm
Playback Functions	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Full Screen, Frame Play, Frame Rewind, Digital Zoom
Backup Mode	USB Device/Network

Network

Interface	9 RJ45 10M/100M Adaptive Ethernet Interface
Incoming Bandwidth	60MB
Network Functions	TCP/IP, HTTP, UPP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, p2p
Onvif Version	Support Onvif 2.8
Web Browser	IE8-11, Google Chrome (Lower Than Ver44), Firefox (Lower Than Ver53)
CMS Software	Support Windows 7/Windows 8/Windows 10/MAC OS
Cloud Support (P2P)	Yes
Smart Phone	IPhone, IPad, Android, Android Pad
POE	8 Independent 100Mbps POE Network Interfaces (Output PowerAT mode 30W, AF Mode 15W Per Interface), 45/78 Line Order, Total Power Output 100W, Support Plug & Play

Storage

Interface Type	1SATA Hard Disk Interface (2.5" /3.5" SATA)
Capacity	Up To 8TB Capacity

General

USB Interface	2 USB 2.0 Interfaces
Power Supply	DC 52V/2500mA 56W (Without Hard Disk & POE)
Working Environment	-10 ~ 55°C 10 ~ 90%RH
Dimension W×DxH	Φ260x215x43mm
Weight	2.0kg (Without HDD)





U·LINK

POWERING THE FUTURE

Email:
info@u-link.uk

Address:
Sydney House, 62 Lancaster Way, Ely,
Cambridgeshire, CB6 3NW, UK

Website:
https://u-link.uk